



Receptacles

Standard self-locking terminals

| Figure | Part number | Wire size mm ² (AWG) | Ø Insulation (mm) | For male (mm) | 00 | 01 | 30 | 31 | Material thickness (mm) | Winding number |
|--------|----------------|---------------------------------------|-------------------------|------------------|-------|--------------|--------|---------------|-------------------------------|-------------------|
| | | | | | Brass | Brass Pre-Sn | Bronze | Bronze Pre-Sn | | |
| | 4940.** | 0,5-1,3 (20-16) | 2,3-3,3 | 6,3x0,8 | • | • | • | • | 0,4 | 1800 |
| | 4942.** | 0,7-2 (18-14) | 2,4-3,2 | | • | • | • | • | | |
| | 4944.** | 2,5-4 (14-12) | 3,4-5 | | • | • | • | • | | |
| | 4946.** | 3,3-6 (12-10) | 3,4-5,1 | | • | • | • | • | | 1300 |



Receptacle housings

| Figure | Part number | Ways | Dimensions | PA66V2 | Natural | |
|--------|-----------------|------|------------|--------|---------|--|
| | | | | 10 | | |
| | 1 way Connector | | | | | |
| | 26370** | 1 | 5,5-9-24 | • | | |

Receptacles

Receptacle Connectors

| Figure | Part number | Ways | Dimensions | PA66V2 Natural |
|--------|-------------|------|-------------|----------------|
| | 26372** | 2 | 15,2-8,8-24 | • |

2 ways Connector