



## Receptacles for connector

### 2.8 mm Timer Terminal

Figure	Part number	Wire size mm <sup>2</sup> (AWG)	Ø Insulation (mm)	Brass Pre-Sn	Bronze	Bronze Pre-Sn	Material thickness (mm)	Winding number
				01	30	31		
	<b>8400.**</b>	<b>0,5-1</b> (20-18)	1,5-2,1	•		•	0,32	5000
	<b>8401.**</b>		3,4 SEAL			•		3500
	<b>8402.**</b>	<b>1-1,5</b> (18-16)	1,9-2,4	•		•		4500
	<b>8403.**</b>		3,4 SEAL			•		3500
	<b>8407.**</b>	<b>1-2,5</b> (18-14)	2,4-3,6	•		•		4000
	<b>8404.**</b>	<b>1,5-2,5</b> (16-14)	3-4,3	•		•		3500
<b>8405.**</b>	<b>2-3</b> (16-12)			•	•	•		



### Receptacle Connectors

Figure	Part number	Ways	PA66V2 Black	PA66V2 Brown
			•	•
	Central Polarization			
	<b>2100917</b>	8		•
	Left Polarization			
	<b>2100915</b>	8	•	

## Receptacles for connector

### 6.3 mm Timer terminals

Figure	Part number	Wire size mm <sup>2</sup> (AWG)	Ø Insulation (mm)	Brass	Brass Pre-Sn	Bronze	Bronze Pre-Sn	Material thickness (mm)	Winding number
				00	01	30	31		
	<b>8435.**</b>	<b>0,2-0,6</b> (24-20)	1,4-2,1	•	•	•	•	0,32	3500
	<b>8437.**</b>	<b>0,5-1</b> (20-18)	1,5-2,1	•	•	•	•		
	<b>8437F**</b>		FLR	•	•	•	•		
	<b>8441.**</b>	<b>0,5-1,5</b> (20-16)	1,8-3,3	•	•	•	•	0,32	
	<b>8441F**</b>		•	•	•	•	0,4		
	<b>8442.**</b>	<b>0,75-1,5</b> (18-16)	1,8-2,3	•	•	•	•	0,32	
	<b>8445.**</b>		3-4,3	•	•	•	•	0,4	
	<b>8445F**</b>	•		•	•	•			
	<b>8449.**</b>	<b>2-3</b> (16-12)		•	•	•	•		

### Receptacle Connectors

Figure	Part number	Ways	Dimensions	To terminal	PA66V2 Natural	PA66V2 White	
					10	11	
	8 ways Connector						
	<b>26398**</b>	8	9-40-25	8437.01	•		
	12 ways Connector						
	<b>26385**</b>	12	8,8-61-24	8437.01	•	•	

## Receptacles for connector

### Receptacle Connectors

Figure	Part number	Ways	Dimensions	To terminal	PA66V2 Natural	PA66V2 White
	<b>26368**</b>	8	9-40-25	8437.01	<input checked="" type="checkbox"/>	<input type="checkbox"/>

8 ways connector with locking