

PRODUCT DATASHEET



22815** 2.8 (.110) TYPE SERIES · RECEPTACLES

1



Specification

Receptacle housings

Ways

Thermal Characteristics Glow Wire Test Flammability Glow Wire **RTI** electrical Flammability Index (IEC60695-2-12) Part nr. Raw material Color Class (GWT) (Max. Operating (UL 94) (IEC60695-2-11) Temp.) 2281510 PA66V2 Natural V2 (T.B.D.) 850ºC 105ºC 105ºC V2 (T.B.D.) 800ºC 2281515 PA66V2 Black (T.B.D.) 130ºC 2281540 NO FLAME V2 960ºC Natural


For other materials and colors ask to: info@escubedo.com

Compatible terminals

4809.**, 4809G**, 4809K**, 4811.**, 4811E**, 4811G**

Insertion / Withdrawal forces		2281510 / 15 / 40
	1st Insertion (max)	5N
	1st Withdrawal (min, primary lock only)	35N

Drawing



(T.B.D.): To be determined

Disclaimer

Data obtained from Escubedo Laboratory essays, using own methodology, cablings, equipment and original crimping tools, done in laboratory conditions and following the indicated standards, errors and omissions excepted. This document has no contractual meaning and it is publicised only for informative purposes. It can be changed without prior notice. The end customer has the sole responsibility to check these characteristics in its environment and with its own components, manufacturing methods and equipment. See also the full range product overview if available. For further information please visit our web site or contact us

Rev. Nr.	Concept	Date	Created/Revised	Approved	
A4	Change company name and logo	2021-10-21	Laboratory Dept.	E. Roura	
A3	Update [Compatible terminals]	2019-02-27	Laboratory Dept.	E. Roura	
A2	Update datasheet (Specification)	2018-07-13	Laboratory Dept.	E. Roura	
A1	Datasheet generated automatically [A1]	2018-06-20	Engineering Department	X.Menac	
Escubedo Connection Systems, S.A.U. · Ctra. de Girona-Olot Km. 35,5 · 17843 Riudellots de la Creu · Girona · Spain Tel.: 34 972 171 706 · Fax: +34 972 171 714 · <u>info@escubedo.com</u> · <u>www.escubedo.com</u>					