

PRODUCT DATASHEET



5367.**

8 (.315) TYPE SERIES - FLAGS FOR CONNECTOR



Specification Low insertion

For male (mm) 7,9x0,75

Wire size mm² (AWG) 0,5-1 (20-18)

Ø Insulation (mm) 1,6-2,3

Materials, temperature and contact resistance

Part nr.	Material	Finishing	Max. Temp. (°C)
5367.00	Brass	Natural	110
5367.01	Brass	Pre-tin-plated	120

Material thickness (mm)

Insertion / Withdrawal forces

	5367.00 / 01		
1st Insertion (max)	20N		
1st Withdrawal (max)	20N		
10th Withdrawal (min)	10N		

Application tool MN5366

Crimping parameters & pull out force

Wire section (±10%)	Conductor		Insulator	Pull-out force (N)	
	Height (mm)	Width (mm)	Width (mm)	(14)	
0.50 mm ²	1.20 (±0.03)	2.54 (±0.03)	3.16 (±0.10)	56N @ 60s	
0.75 mm ²	1.30 (±0.05)	2.55 (±0.05)	3.18 (±0.10)	84N @ 60s	
1.00 mm ²	1.40 (±0.05)	2.57 (±0.05)	3.18 (±0.10)	108N @ 60s	

Values only valid for the application tool specified upwards. The insulator widths are only indicative as they are dependent on the sheath thickness of the wire used.

3500


Compatible connectors 28054**, 28056**

Approvals

Winding number



Drawing





Escubedo Connection Systems, S.A.U. · Ctra. de Girona-Olot Km. 35,5 · 17843 Riudellots de la Creu · Girona · Spain Tel.: 34 972 171 706 · Fax: +34 972 171 714 · info@escubedo.com · www.escubedo.com

5367.** Rev. A2 1/2



PRODUCT DATASHEET



5367.** 8 (.315) TYPE SERIES - FLAGS FOR CONNECTOR



Data obtained from Escubedo Laboratory essays, using own methodology, cablings, equipment and original crimping tools, done in laboratory conditions and following the indicated standards, errors and omissions excepted. This document has no contractual meaning and it is publicised only for informative purposes. It can be changed without prior notice. The end customer has the sole responsibility to check these characteristics in its environment and with its own components, manufacturing methods and equipment. See also the full range product overview if available. For further information please visit our web site or contact us

Rev. Nr.	Concept	Date	Created/Revised	Approved
A2	Change company name and logo	2021-10-21	Laboratory Dept.	E. Roura
A1	Datasheet generated automatically [A1]	2019-01-18	Laboratory Dept.	E. Roura

Escubedo Connection Systems, S.A.U. · Ctra. de Girona-Olot Km. 35,5 · 17843 Riudellots de la Creu · Girona · Spain Tel.: 34 972 171 706 · Fax: +34 972 171 714 · info@escubedo.com · www.escubedo.com