

8904.** SPECIAL TERMINALS · END CONNECTORS



Specification Without insulation support

Din Esp

Wire size mm² (AWG) 0,75-2 (18-14)

Materials, temperature and contact resistance


Part nr.	Material	Finishing	Max. Temp. (°C)
8904.00	Brass	Natural	110
8904.02	Brass	Tin plated	120
8904.24	Steel	Nickel-plated	300

Material thickness (mm) 0,3

Application tool MN8904

Wire strip length 6.5 (±0.5) mm

Crimping parameters & pull out force

Wire section (±10%)	Conductor 		Pull-out force (N)
	Height (mm)	Width (mm)	
0.75 mm ²	1.55 (±0.05)	1.80 (±0.05)	84N @ 60s
1.00 mm ²	1.65 (±0.05)	1.84 (±0.05)	108N @ 60s
1.50 mm ²	1.75 (±0.05)	1.84 (±0.05)	150N @ 60s
2.00 mm ²	1.90 (±0.05)	1.88 (±0.05)	150N @ 60s



Values only valid for the application tool specified upwards. The insulator widths are only indicative as they are dependent on the sheath thickness of the wire used.

Winding number 40000

Approvals



Drawing



8904.**
SPECIAL TERMINALS · END CONNECTORS**Disclaimer**

Data obtained from Escubedo Laboratory essays, using own methodology, cablings, equipment and original crimping tools, done in laboratory conditions and following the indicated standards, errors and omissions excepted. This document has no contractual meaning and it is publised only for informative purposes. It can be changed without prior notice. The end customer has the sole responsibility to check these characteristics in its environment and with its own components, manufacturing methods and equipment. See also the full range product overview if available. For further information please visit our web site or contact us

Rev. Nr.	Concept	Date	Created/Revised	Approved
A2	Change company name and logo	2021-10-21	Laboratory Dept.	E. Roura
A1	Datasheet generated automatically [A1]	2018-10-01	Laboratory Dept.	E. Roura

Escubedo Connection Systems, S.A.U. · Ctra. de Girona-Olot Km. 35,5 · 17843 Riudellots de la Creu · Girona · Spain
Tel.: 34 972 171 706 · Fax: +34 972 171 714 · info@escubedo.com · www.escubedo.com